

The VersaDrive Countersink is a premium quality countersink with fully ground flutes and Titanium coating to help reduce wear and blunting.

VersaDrive Countersinks have a patented non-slip, Hex shank suitable for use in any standard 1/2" drill chuck for cordless or pistol drills or used with a VersaDrive Rapid Lock adapter for use in a wide range of powertools such as Magnetic Drills.

Utilise the convenience and power of an impact wrench to quickly debur and countersink holes up to 16.5mm with minimal torque kick-back against the operator.



Features & Benefits

- For Countersunk Bolt Heads
- High-Grade Tool Steel for high accuracy & long life
- Safer use with minimal kickback
- GoldMax low friction Titanium Coating to stop burn out
- Specially hardened for impact wrench use up to 16.5mm
- 1st Impact rated countersinks on the market

RECOMMENDED FOR USE WITH:

Rotary Drills
Magnet Drills
Pillar Drills

CAN ALSO BE USED WITH:

Impact Wrenches/Drivers
(up to 16.5mm)
SDS+ Adapter
Extension Arbor



ADAPTERS



Use with any
standard drill
chuck



Magnet Drill Adapter
111035-01
Page 13



VersaDrive Impact Adapters
111026-014A & 111130-012A
Page 12



SDS+ Adapter
112010-01
Page 14



Extension - 300mm
111015-300
Page 14

Quick Guide

- Optimum life and performance when used with rotary pistol drills or drill presses
- Up to 16.5mm can be used on impact wrench & impact drivers for fast cutting performance
- Suitable for harder materials such as stainless steel when used at reduced RPM
- Not for use on plasma cut or flame cut holes
- Use appropriate lubrication and correct RPM to achieve long tool life

Watch the video &
find more info online



VersaDrive Countersinks

	Part No	D Ø mm	Ø d1 mm	l1 mm	L mm	Countersunk Screw	Point Angle
Metric - 90°	603060-0063	6.3mm	1.5	17	45	M3	90°
	603060-0083	8.3mm	2.0	22	50	M4	90°
	603060-0104	10.4mm	2.5	22	50	M5	90°
	603060-0124	12.4mm	2.8	28	56	M6	90°
	603060-0165	16.5mm	3.2	32	60	M8	90°
	603060-0205	20.5mm	3.5	35	63	M10	90°
	603060-0250	25mm	3.8	39	67	M12	90°
	603060-0310	31mm	4.2	43	71	M16	90°
Inch - 82°	603065-0100	1/4"	1/16	7/64	1-27/32	-	82°
	603065-0200	3/8"	7/64	5/32	2-3/64	-	82°
	603065-0300	1/2"	7/64	7/32	2-9/32	-	82°
	603065-0400	5/8"	1/8	9/32	2-7/16	-	82°
	603065-0500	3/4"	1/8	11/32	2-9/16	-	82°
	603065-0600	1"	11/64	31/64	2-23/32	-	82°

Impact Wrenches	Impact Drivers	SDS Drill (Rotary)	Cordless Drill	Pillar Drill Press	Magnet Drill
-----------------	----------------	--------------------	----------------	--------------------	--------------

Powertool Recommendations (Mild Steel Material)					
●	●	○	●	●	●
●	●	○	●	●	●
●	●	○	●	●	●
●	●	○	●	●	●
○	○	○	●	●	●
×	×	○	●	●	●
×	×	○	●	●	●
×	×	○	●	●	●

●	●	●	●	●	●
●	●	●	●	●	●
●	●	●	●	●	●
●	●	●	●	●	●
○	○	○	●	●	●
×	×	○	●	●	●
×	×	○	●	●	●

● Optimal ○ Possible (Refer to data sheet)
× Not Recommended

VersaDrive Countersink Set

Part No:	Set Contents
603060-5SET	Set contains: 12.4, 16.5, 20.5, 25, 31mm VersaDrive 90° Countersink Bits
603065-5SET	Set contains: 3/8", 1/2", 5/8", 3/4", 1" VersaDrive 82° Countersink Bits



COMPLETE COUNTERSINK RANGE - P78

