

Model:

RH-602 RING ROLLER

DIMAKIN

FEATURES:

- Compact design
- Two driven rolls
- Hydraulic top roll adjustment
- Standard segmental flat tooling
- Custom tooling available
- Lateral guide rolls
- Horizontal and vertical positions

**SPECIFICATIONS**

| | |
|-------------------------------|--------------------------------|
| FLAT BAR (HARD WAY) ●● | 60mm x 10mm Ø900mm |
| FLAT BAR (EASY WAY) ●● | 80mm x 15mm Ø700mm |
| SOLID SQUARE ●● | 35mm x 35mm Ø1000mm |
| SOLID ROUND ●● | Ø35mm Ø900mm |
| TUBE ● | Ø60mm x 2mm Ø1100 |
| PIPE ● | Ø48.3mm x 2.9mm Ø1000mm |
| RECTANGULAR HOLLOW SECTION ●● | 50mm x 40mm x 3mm |
| SQUARE HOLLOW SECTION ●● | 40mm x 40mm x 3mm |
| ANGLE (TOE OUT) ● | 50mm x 50mm x 5mm Ø800mm |
| ANGLE (TOE IN) ● | 50mm x 50mm x 5mm Ø950mm |
| T-SECTION (TOE OUT) ●● | 50mm x 5mm x Ø700mm |
| T-SECTION (TOE IN) ●● | 50mm x 5mm x Ø900mm |
| T-SECTION (TOE UP) ●● | 50mm x 5mm x Ø900mm |
| CHANNEL SECTION (TOES OUT) ●● | UPN 60 Ø900 |
| CHANNEL SECTION (TOES IN) ●● | UPN 60 Ø1300 |
| POWER | 2.6kW 3.5hp |
| RPM | 13.6/27.2 |
| TOOL Ø | 146/98 |
| SHAFT Ø | 50/50 |
| SECTION MOD (CM3) | 16 |
| SHIPPING DIMENSIONS | 330kgs 1300mm x 800mm x 1500mm |

- Standard Rolls
- One set of rolls is required for each tube OD
- Special rolls for thin wall profiles
- Special profile