

**Model:**

RH-603 RING ROLLER

**DIMAKIN****FEATURES:**

- Compact design
- Three driven rolls
- Hydraulic top roll adjustment
- Standard segmental flat tooling
- Custom tooling available
- Lateral guide rolls
- Horizontal and vertical positions

**SPECIFICATIONS**

FLAT BAR (HARD WAY) ●●	60mm x 10mm Ø800mm
FLAT BAR (EASY WAY) ●●	80mm x 15mm Ø600mm
SOLID SQUARE ●●	35mm x 35mm Ø800mm
SOLID ROUND ●●	Ø35mm Ø700mm
TUBE ●	Ø60mm x 2mm Ø1000
PIPE ●	Ø60.3mm x 2.9mm Ø1000mm
RECTANGULAR HOLLOW SECTION ●●	60mm x 30mm x 3mm
SQUARE HOLLOW SECTION ●●	45mm x 45mm x 3mm
ANGLE (TOE OUT) ●	50mm x 50mm x 5mm Ø600mm
ANGLE (TOE IN) ●	50mm x 50mm x 5mm Ø700mm
T-SECTION (TOE OUT) ●●	60mm x 5mm x Ø700mm
T-SECTION (TOE IN) ●●	60mm x 5mm x Ø900mm
T-SECTION (TOE UP) ●●	60mm x 5mm x Ø900mm
CHANNEL SECTION (TOES OUT) ●●	UPN 60 Ø800
CHANNEL SECTION (TOES IN) ●●	UPN 60 Ø1200
POWER	3.7kW 5hp
RPM	12
TOOL Ø	146/98
SHAFT Ø	45/45
SECTION MOD (CM3)	16
SHIPPING DIMENSIONS	500kgs 1300mm x 800mm x 1500mm

- Standard Rolls
- One set of rolls is required for each tube OD
- Special rolls for thin wall profiles
- Special profile