

Model:

RH-703 RING ROLLER

DIMAKIN

FEATURES:

- Compact design
- Three driven rolls
- Hydraulic top roll adjustment
- Standard segmental flat tooling
- Custom tooling available
- Lateral guide rolls
- Horizontal and vertical positions

**SPECIFICATIONS**

FLAT BAR (HARD WAY) ●●	70mm x 12mm Ø1800mm
FLAT BAR (EASY WAY) ●●	70mm x 20mm Ø1000mm
SOLID SQUARE ●●	45mm x 45mm Ø1000mm
SOLID ROUND ●●	Ø45mm Ø1000mm
TUBE ●	Ø70mm x 3mm Ø3000
PIPE ●	Ø76.1mm x 3.2mm Ø2500mm
RECTANGULAR HOLLOW SECTION ●●	70mm x 30mm x 3mm
SQUARE HOLLOW SECTION ●●	50mm x 50mm x 3mm
ANGLE (TOE OUT) ●	50mm x 50mm x 5mm Ø700mm
ANGLE (TOE IN) ●	50mm x 50mm x 5mm Ø700mm
T-SECTION (TOE OUT) ●●	70mm x 5mm x Ø700mm
T-SECTION (TOE IN) ●●	70mm x 5mm x Ø900mm
T-SECTION (TOE UP) ●●	70mm x 5mm x Ø900mm
CHANNEL SECTION (TOES OUT) ●●	UPN 80 Ø1200
CHANNEL SECTION (TOES IN) ●●	UPN 80 Ø1200
POWER	5.5kW 7hp
RPM	11
TOOL Ø	170/108
SHAFT Ø	55/55
SECTION MOD (CM3)	20
SHIPPING DIMENSIONS	650kgs 1300mm x 890mm x 1550mm

- Standard Rolls
- One set of rolls is required for each tube OD
- Special rolls for thin wall profiles
- Special profile