Cartridge Filter, Stationary

Art. No.: 83 200 104



Technical Data

Filter	
Filter stages	1
Filter method	Cleanable filter
Filter cleaning method	Rotating nozzle
Filter surface	8 m²
Type of filter	Filter cartridge
Filter material	ePTFE membrane
Filter efficiency	> 99.9 %
Dust classification	М
Basic data	
Extraction capacity	2 x 700 m ³ /h
Max. fan performance	3000 m³/h
Maximum vacuum	3000 Pa
Dimensions (w x t x h)	655 x 655 x 1355 mm
Weight	142 kg
Motor power	1.5 kW
Power supply	3 x 400 V / 50 Hz
Rated current	3.5 A
Noise level	71 dB(A)
Additional information	
Fan type	Radial fan
Compressed air supply	5 - 6 bar
Quantity of extraction arms	2
Exhaust arm type	flexible exhaust arm
Diameter extraction arm	150 mm
Length of exhaust arm	6 m
Compressed air reservoir	25
Capacity Dust collection container	11

Applications

- · High levels of smoke and particles
- Non-stop operation
- · Two exhaust arms available

Benefits

- · High efficiency due to automatic filter cleaning
- Less need to adjust the exhaust arm due to flowoptimised exhaust hood design
- Best health protection for employees by use of KemTex® ePTFE filter cartridges with surface filtration
- Low air consumption due to differential pressurecontrolled cleaning
- · Space-saving solution due to two extraction arms
- Possibility of working in two alternating places due to dampers in the extraction hood

Properties


- · 360 degrees rotating exhaust hood with damper
- · Automatic filter cleaning, pressure-controlled
- · KemTex® ePTFE filter cartridges
- · Automatic Start-Stop (optional)
- · Lighting in the hood (optional)
- · Arm from 5 m with boom
- · Available with two arms
- · Silencer
- · Control box


Accessories


- · Automatic start-stop
- · Workplace lighting incl. on/off switch at the hood











Technical Data

Dimensions	
А	1332 mm
В	755 mm
С	701 mm
D	551 mm
E	715 mm
F	337 mm
G	898 mm
Н	97 mm
1	400 mm
J	218 mm
K	151 mm
L	158 mm



Dimensions

М	271 mm
***	27

