SAFETY DATA SHEET

Version #: 1,0
Issue date: 16-November-2022
Revision date: 16-November-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	AMBERCLENS
Registration number	-
Synonyms	None.
Product code	UDS000360AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaners - Heavy duty
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries UK Ltd.
Address	Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com

1.4. Emergency telephone number

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

Austria National Poisons Information Centre	+431 406 4343 (Available 24 hours a day.)
Belgium National Poisons Control Center	070 245 245 (Available 24 hours a day.)
Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays))

Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided.)
Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day.)
Romania Număr de telefon care poate fi apelat în caz de urgență:	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentafloreasca.ro
Romania	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.

Health hazards

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms



Signal word Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H319	Causes serious eye irritation.

Precautionary statements

Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information According to Regulation (EC) No. 648/2004 on Detergents, as amended; Contains: Benzyl alcohol Limonene
Perfumes; anionic surfactants <5%
non-ionic surfactants <5%
aliphatic hydrocarbons 5-15%

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER	1 - 5	107-98-2 203-539-1	01-2119457435-35	603-064-00-3	#
Classification: Flam. Liq. 3;H226, STOT SE 3;H336					
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1 - 5	- 926-141-6	01-2119456620-43	-	
Classification: Asp. Tox. 1;H304					
Supplemental Hazard Statement(s): EUH066					
Propan-2-ol; Isopropyl alcohol; Isopropanol	1 - 5	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt	<3	137-16-6 205-281-5	01-2119527780-39	-	
Classification: Acute Tox. 2;H330;(ATE: 0,5 mg/l), Skin Irrit. 2;H315, Eye Dam. 1;H318, Aquatic Chronic 3;H412					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).
ATE: Acute toxicity estimate.
M: M-factor
PBT: persistent, bioaccumulative and toxic substance.
vPvB: very persistent and very bioaccumulative substance.
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria

Components	Type	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAK)	200 ppm

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	187 mg/m3
		50 ppm
	MAK	187 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	MAK	500 mg/m3
		200 ppm
	STEL	2000 mg/m3
		800 ppm

Belgium. Exposure Limit Values

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	369 mg/m3
		100 ppm
	TWA	184 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
	TWA	980 mg/m3

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	MAC	375 mg/m3
		100 ppm
	STEL	568 mg/m3
		150 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	MAC	999 mg/m3
		400 ppm
	STEL	1250 mg/m3

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
		500 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	980 mg/m3
		400 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	550 mg/m3
	TWA	270 mg/m3
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Ceiling	1000 mg/m3
	TWA	500 mg/m3

Denmark. Exposure Limit Values

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TLV	185 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	490 mg/m3
		200 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3
		150 ppm
	TWA	370 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	620 mg/m3

Finland. Workplace Exposure Limits

Components	Type	Value
		250 ppm
	TWA	500 mg/m3
		200 ppm

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	VLE	375 mg/m3
		100 ppm
	VME	188 mg/m3
		50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	VLE	375 mg/m3
Regulatory status: Regulatory binding (VRC)		
		100 ppm
Regulatory status: Regulatory binding (VRC)		
	VME	188 mg/m3
Regulatory status: Regulatory binding (VRC)		
		50 ppm
Regulatory status: Regulatory binding (VRC)		
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	VLE	980 mg/m3
Regulatory status: Indicative limit (VL)		
		400 ppm
Regulatory status: Indicative limit (VL)		

Germany

Components	Type	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TWA	370 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	AGW	370 mg/m3
		100 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	AGW	500 mg/m3
		200 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	1080 mg/m3
		300 ppm
	TWA	360 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
	TWA	375 mg/m3
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
	TWA	500 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	185 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	490 mg/m3
		200 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
	TWA	350 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	300 mg/m3
		75 ppm
	TWA	190 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
	TWA	375 mg/m3
		100 ppm

Netherlands

Components	Type	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAC)	1200 mg/m3

Netherlands. OELs (binding)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	563 mg/m3
	TWA	375 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TLV	180 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	245 mg/m3
		100 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	360 mg/m3
	TWA	180 mg/m3
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1200 mg/m3
	TWA	900 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	100 ppm
	TWA	50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
	TWA	200 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	500 mg/m3
		203 ppm
	TWA	200 mg/m3
		81 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
	TWA	500 mg/m3
		200 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	568 mg/m3
		150 ppm
	STEL	300 mg/m3
		75 ppm
	TWA	190 mg/m3
		50 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	720 mg/m3
		200 ppm
	TWA	360 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3
		500 ppm
	TWA	999 mg/m3
		400 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
		150 ppm
	TWA	375 mg/m3
		100 ppm

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	50 mg/l	Acetone	Urine	*
	50 mg/l	Acetone	Blood	*
	0,86 umol/l	Acetone	Urine	*
	0,86 umol/l	Acetone	Blood	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	15 mg/l	1-Methoxypropan-2-ol	Urine	*
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
	25 mg/l	ACETON	Blood	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	430 µmol/l	Acetone	Urine	*
	25 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	20 mg/l	1-METHOXYPROPANOL-2	Urine	*
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
	25 mg/l	ACETON	Blood	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

Components	Value	Assessment factor	Notes
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)			
Long-term, Systemic, Dermal	78 mg/kg bw/day	16,8	Repeated dose toxicity
Long-term, Systemic, Inhalation	43,9 mg/m3		Repeated dose toxicity

Long-term, Systemic, Oral	33 mg/kg bw/day	28	Repeated dose toxicity
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m3	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)			
Long-term, Systemic, Dermal	183 mg/kg bw/day	10,08	Repeated dose toxicity
Long-term, Systemic, Inhalation	369 mg/m3		Repeated dose toxicity
Short-term, Local, Inhalation	553,5 mg/m3		Neurotoxicity
Short-term, Systemic, Inhalation	553,5 mg/m3		Neurotoxicity
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m3	1	

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)			
Freshwater	10 mg/l	100	
Sediment (freshwater)	52,3 mg/kg		
Soil	4,59 mg/kg		
STP	100 mg/l	10	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Freshwater	140,9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		
Soil	28 mg/kg		

Exposure guidelines

Austria MAK: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Belgium OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Bulgaria OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Cyprus OEL: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Can be absorbed through the skin.

Czech Republic PELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Denmark GV: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Estonia OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

EU Exposure Limit Values: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Finland Exposure Limit Values: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

France INRS: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Greece OEL: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Hungary OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Can be absorbed through the skin.

Iceland OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Can be absorbed through the skin.

Ireland Exposure Limit Values: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Can be absorbed through the skin.

Italy OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Danger of cutaneous absorption

Latvia OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Lithuania OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Luxembourg OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Malta OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Netherlands OELs (binding): Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Romania OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Slovakia OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Spain OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

Sweden Threshold Limit Values: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

UK EH40 WEL: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type ABEK)
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol.
Colour	Colourless to yellow.
Odour	Characteristic odor.
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	82 °C (179,6 °F)
Flammability	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	0,6 %
Explosive limit – upper (%)	15 %
Flash point	12,0 °C (53,6 °F)
Auto-ignition temperature	225 °C (437 °F)
Decomposition temperature	Not available.
pH	10
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Soluble in water
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapour pressure	Not available.
Density and/or relative density	
Relative density	0,96 g/cm3 20 °C
Vapour density	Not available.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes	No relevant additional information available.

9.2.2. Other safety characteristics

Evaporation rate	Not available.
VOC	221 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.

10.6. Hazardous decomposition products Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)		
Acute		
Dermal		
LD50	Rabbit	13 g/kg
Inhalation		
LC50	Rat	54,6 mg/l, 4 Hours
Oral		
LD50	Rat	5,71 g/kg
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt (CAS 137-16-6)		
Acute		
Inhalation		
LC50	Rat	1 mg/l
Oral		
LD50	Rat	5001 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	> 5000 mg/m3, 8 h
Oral		
LD50	Rat	> 5000 mg/kg
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		
Acute		
Inhalation		
LC50	Rat	> 25000 mg/m3, 6 h

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance information Not available.

11.2. Information on other hazards

Endocrine disrupting properties The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information May cause allergic respiratory and skin reactions.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)			
Aquatic			
Acute			
Algae	EC50	Algae	> 1000 mg/l, 72 h
Crustacea	EC50	Daphnia	> 1000 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	> 1000 mg/l, 96 h
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt (CAS 137-16-6)			
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	29,7 mg/l, 48 hours
Fish	LC50	Zebra fish	107 mg/l, 96 hours
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Aquatic			
Acute			
Crustacea	EC50	Daphnia	1000 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	1000 mg/l, 96 h
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Aquatic			
Acute			
Crustacea	LC50	Brine shrimp (Artemia salina)	> 10000 mg/l, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER	-0,49
Propan-2-ol; Isopropyl alcohol; Isopropanol	0,05

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 0

12.8. Additional information

Estonia Dangerous substances in soil Data

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.
Label(s)	2.1
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	D
ADR/RID - Classification code:	5F
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.

14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.

ADR; IATA; IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
GWP: Global Warming Potential.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TLV: Threshold Limit Value.
TWA: Time Weighted Average.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
VOC: Volatile organic compounds.
vPvB: Very persistent and very bioaccumulative.
STEL: Short-term Exposure Limit.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.