

MICRO-TORCH CK EXCLUSIVE

- 70 or 140 Amps at 100% duty cycle, low profile micro torch
- 45°, 90° and 180° interchangeable heads
- Clear Pyrex nozzle fits on all three heads
- Super-Flex® cable assembly makes it easier to manipulate the torch
- Tungsten gauge and wrench makes installing tungsten easy



70 amps
Air Cooled
or
140 amps
Water Cooled

MR70 AIR-COOLED MICRO TORCH

HEAD STYLE	CABLE	LENGTH	PART NUMBER
Rigid Head w/o Valve	3 Piece	12-1/2 ft. (3.8m)	MR712SF
		25 ft. (7.6m)	MR725SF

MR140 WATER-COOLED MICRO TORCH


HEAD STYLE	CABLE	LENGTH	PART NUMBER
Rigid Head w/o Valve	3 Piece	12-1/2 ft. (3.8m)	MR1412SF
		25 ft. (7.6m)	MR1425SF

KIT INCLUDES:

- 45°, 90° and 180° interchangeable heads
- .040" (1.0mm), 1/16" (1.6mm) and 3/32" (2.4mm) collets
- 3 Clear Pyrex nozzles
- 3 pieces of Tungsten
- Tungsten Stick-Out Gauge and Wrench

SPECIFICATIONS:

Neck Diameter0.312" (7.92mm)
 Neck Length..... 3.100" (78.74mm)
 Cup Diameter.....0.360" (9.14mm)
 Cup Length 0.600" (15.24mm)



TUNGSTEN STICK-OUT GAUGE

- Loosen knurled lock nut
- Turn threaded gauge rod to adjust gauge depth (markings are in 1/16th inch increments)
- Lock gauge by turning knurled lock nut firmly against the gauge body

TUNGSTEN SIZES:



Actual sizes shown

SPECIFICATIONS:

Length..... 0.9" (22.86mm)
 Grind..... 20° Grind
 Diameter..... .040" (1.0mm)
 1/16" (1.6mm)
 3/32" (2.4mm)